

Maintaining the **NATURAL TIMBER LOOK** *Low Maintenance & Environmentally Friendly*

BioWood Fire Retardant Composite Decking

Why you should choose BioWood Composite Decking...

- > Lightweight and durable
- > Termite resistant
- > Fire retardant and water resistant
- > Mould and mildew resistant
- > An added value to your investment
- > Easy installation (concealed system)
- > A proven time-tested product in Australia
- > Can be re-sanded and re-sealed
- > No splinters, cracks or rot
- > Ideal for residential and commercial use

*This product has a 7 year limited warranty.
Refer to our website terms and conditions
of warranty details**



Spotted Gum*



Weather Wood*



Red Cedar*



Decking Profile

Product Code: DB14028
Spec: 140 x 28 x 5400 or 5700mm

Product Code: DB09028
Spec: 90 x 28 x 5400 or 5700mm

* Colours shown are within the limits of printing.



What is BioWood Composite Wood Decking?

BioWood Composite Wood Decking is a proprietary composite made by combining wood waste with polymer and additives. It is this blend that gives BioWood Composite Wood Decking its unique benefits over solid timber and other olefin (Polyethylene and Polypropylene) composite products. BioWood Composite Wood Decking looks and feels just like timber but it is sustainable and 100% recyclable.

The BioWood Composite Wood Decking "EDGE"?

BioWood Composite Wood Decking, due to its content of wood fibre, contains all the attributes of timber such as its appearance, hardness and warmth underfoot but does not have the inherent shortcomings of solid timber such as cracking, splitting and rot. In addition, when subject to fire, BioWood Composite Wood Decking, unlike timber and many other composites, is non-combustible & self-extinguishing. BioWood Composite Wood Decking is superior in water resistant and multi-functional that can be applied as façade, ceiling and screening application for residential or commercial application.

How durable is BioWood Composite Wood Decking?

BioWood Composite Wood Decking is water and termite resistant and does not promote the growth of mould and mildew. Stains and scratches are also easily dealt with (refer to the maintenance section on the installation guide). UV inhibitors added at the point of manufacture ensure minimum colour fading and maximum service life.

Is BioWood Composite Wood Decking suitable around pools & safe?

BioWood Composite Wood Decking is very much at home around pools, spas, boardwalks and all marine environments as it is impervious to salt water although we also recommend with pool or marine application to apply a water-based anti-slip coating. Also, as BioWood Composite Wood Decking will not splinter, it is ideal for children and bare feet!

How difficult is BioWood Composite Wood Decking to install & does it need to be coated?

BioWood Composite Wood Decking is simple and cost effective to lay, when installed in accordance with the installation guide, which is available as a hard copy or from the BioWood Composite Wood Decking website. Normal wood-working tools can be used to drill, rout, sand and rip BioWood Composite Wood Decking to create the perfect deck. Waste is kept to a minimum as BioWood Composite Wood Decking is supplied in 5.4 or 5.7 metre lengths. Concealed connectors are used to provide a blemish free finish which avoids additional maintenance and safety problems such as nail popping. BioWood Composite Wood Decking products are supplied uncoated. Once installed we recommend that you apply two coats of water based UV stabilised coating. Like all building products, it is recommended that good safety disciplines be adhered to by providing adequate ventilation when machining BioWood Composite Wood Decking to avoid inhaling dust. BioWood Composite Wood Decking is designed to be installed with a maximum span of 450 mm between joists for residential application. BioWood Composite Wood Decking is NOT intended for use as structural members of deck.

What is the warranty of BioWood Composite Wood Decking?

BioWood Composite Wood Decking products are backed by a 7 year limited warranty.



Biowood Products are sourced through a chain-of-custody forest certification scheme - PEFC

Accessories



Black Plastic Decking Connectors

Product Code: ADC285
Spec: For 28mm decking with 5mm Gap



Cover Mould

Product Code: CMO02806
Spec: 28 x 6 x 5700mm

Manufactured by:



Available at:

Trusted by:



green building council australia



www.biowoodaustralia.com.au | (02) 9644 6766